





Technical Specifications

DESCRIPTION	PDF200AG	PDF290AG	PDF350AG	PDF350AGL	PDF400E	PDF500E
Gross Capacity (Ltrs)	182	282	338	338	442	541
Temperature Range	-18° to -22°C					
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Refrigerant	R290	R290	R290	R290	R404a	R404a
No of Lids (Nos.)	2	2	2	2	2	2
Glass Type	Low Emissive Toughened Glass					
Inner Cabinet	Anodised Stucco Aluminium					
PUF Thickness mm	70	70	70	70	70	70
Overall Dimensions (WxDxH) mm	750x650x833	968x656x925	1224x654x925	1224x654x925	1320x650x888	1570x650x888
Net Weight (Kg)	47	56	73	73	72	110
No of Baskets (Nos.)	2	3	3	3	4	5
Wheels/Legs	Heavy Duty Lockable Castors					

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product images shown are for reference only and a subject to change without prior notice. The product image without prior notice in the subject to change without prior notice. The product image without prior notice in the subject to change without prior notice. The product image without prior notice in the subject to change without prior notice. The prior notice is the subject to change without prior notice in the subject to change without prior notice in the subject to change without prior notice. The prior notice is the subject to change without prior notice in the subject to change without prior notice. The prior notice is the subject to change without prior notice in the subject to change with the subjeactual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.

















