





Technical Specifications

| MODEL NUMBER | KORAL12CGDSR | KORAL18CGDSR | KORAL15CGDGR | KORAL22CGDGR | KORAL30CGDGR |
|--------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| Function | Remote | Remote | Remote | Remote | Remote |
| Size in ft | 4 | 6 | 5 | 7.5 | 10 |
| Temp Range °C | -1°C~7°C | -1°C~7°C | 0°C~+10°C | 0°C~+10°C | 0°C~+10°C |
| Voltage/Frequency | 220VAC~240VAC, 50Hz |
| Rated Current [A] | 1.18 | 1.7 | 3 | 4 | 4.5 |
| Rated Power [W] | 260 | 371 | 100 | 140 | 180 |
| Refrigerant | R404a/R22 | R404a/R22 | R404a/R22 | R404a/R22 | R404a/R22 |
| FEATURES | | | | | |
| Price Ticket Strip | Yes | Yes | Yes | Yes | Yes |
| Shelf Type | 5shelves | 5shelves | 5shelves | 5shelves | 5shelves |
| Glass Door | Yes | Yes | Yes | Yes | Yes |
| Side Panel | Solid Panel | Solid Panel | Glass | Glass | Glass |
| Light | Yes | Yes | Yes | Yes | Yes |
| Temp Display | Digital | Digital | Digital | Digital | Digital |
| Product Dimension(W×D×H) in mm | 1180×750×1930 | 1770×750×1930 | 1500×850×2050 | 2250×850×2050 | 3000×850×2050 |
| Weight in kg | 165 | 245 | 100 | 160 | 220 |

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.

















