





Technical Specifications

MODEL NUMBER	KRYSTA 12C FV/MT/DL	KRYSTA 18C FV/MT/DL	KRYSTA 25C FV/MT/DL
Dimensions (H x D x W)	2060 x 1250 x 750	2060 x 1875 x 750	2060 x 2500 x 750
Temperature Range	FV : +4°C To +6°C	FV:+4°CTo+6°C	FV:+4°CTo+6°C
	DL:+2°CTo+4°C	DL:+2°CTo+4°C	DL:+2°CTo+4°C
	MT : -1°C To +1°C	MT : -1°C To +1°C	MT : -1°C To +1°C
Refrigerant	R134A / R404A / R407F / R449A / R290 / R1270	R134A / R404A / R407F / R449A / R290 / R1270	R134A / R404A / R407F / R449A / R290 / R1270
Electrical Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Climate Class	3 (25°C , 60% RH)	3 (25°C , 60% RH)	3 (25°C , 60% RH)
Display Area (m²)	DL: 3.39 FV: 2.26	DL:5.08 FV:3.39	DL: 6.78 FV: 4.53

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.

















