





Technical Specifications

DESCRIPTION		P6080E-SL	P6080UVE-SL	P6080UVROE-SL
Performance Parameters	Storage Capacity (L)	80	80	80
	Capacity with Comfort Level Water Outlet Temp at 18°C at Rated Condition (L/hr)	60	60	60
	Storage Capacity - Cold	65	65	65
	Storage Capacity - Ambient	15	15	15
	Storage Capacity - Hot	2	2	2
	Total Running Current (A)	7.5	10	12.5
	Total Power (W)	1575	1630	1700
	Thermal Insulation for Tank	PUF	PUF	PUF
	No. of Faucets (Cold/Hot/Plain)	1/1/1	1/1/1	1/1/1
Filtration Stages	No. of Stages for Filter cum Purifier	-	1) Pre-Filtration, 2) Pre-Carbon 3) Post-Filtration"	1) Pre-Filtration, 2) Pre-Carbon 3) Post-Filtration, 4) RO 5) Post-Carbon
UV	UV Purification	-	Yes, Last Stage	Yes, Last Stage
RO System	RO Membrane Rating (L/hr)	-	-	400
	RO Membrane Operating Temperature	-	-	15°C to 45°C
	RO Membrane Flushing	-	-	Every 12 hours
	RO System and Water Cooler Operating Voltage	-	-	220-240 V
Body	Storage Tank Material	SS304	SS304	SS304
	Outer Body Material	Pre Painted Sheet	Pre-Painted Sheet	Pre-Painted Sheet
	Type of Product Construction	Concealed	Concealed	Concealed
	Type of Installation	Indoor	Indoor	Indoor
	Top Lid Type	Hinged	Hinged	Hinged
Dimensions and Net Weight	Dimension (W x D x H) mm	660 x 575 x 1575	660 x 575 x 1575	660 x 575 x 1575
	Net Weight (kg)	55	63	69
	Refrigerant	R134a	R134a	R134a
	Colour Options	Silver	Silver	Silver

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.

















