

Induction Heating Cooker



Model	TS-678
Adjustable power	320W - 2200W
Voltage	220 V - 50 Hz
Dimensions (mm)	340 x 340 x 75
Net Weight	5.2 kgs
Placket size (mm)	318 x 318

Function :

- No more flaming, no more pollution, Create an enjoyable inner environment.
- Enhance the durability of the inner environment by excluding the smoke and hazardous gas.
- With both cable control and built-in panel control is equipped for easy operation.
- 7 power ranges for adjustment. Customize your foodservice facility and revolutionize commercial induction equipment available. Ideal for demonstration cooking, suite service, catering and buffets.
- Thermal efficiency of more than 90%.
- Automatic cookware material suitability check and overheat alarm protection.
- Digital frequency conversional micro-computer system to protect the IGBT.
- High quality IGBT made in Siemens.

TSI-688 2.4 KW

- German Scott Ceran / Logic Control System
- Touch Sensor Control / LCD Display w / 7 Adjust
- 240 min Timer / Auto Cookware Check
- Over Heated Protection / Heat Residue Indicator
- International Safety Approval
- Cut Out 350x280mm / Net W 4.6 Kg
- Ceran Glass 374 x 302 mm



Function :

- With built-in design, adding to the whole arrangement of kitchen more beautiful.
- Digital frequency conversional micro-computer system.
- Energy saving, smoke free, pollution free, safety and easy clean.
- Large VFD/LED displayer screen: clearer to control the cooking state.
- Automatic cookware material suitability checks and overheats alarm protection.
- 7 adjustable fire power: the best cooking power and Thermal efficiency of more than 90%.
- 4 hour 59 minute time-set and 24 hour 59 minute schedule time-set.
- 1-99 minute digital time-set with automatic shut off.
- CERAN Ceramic-glass cooktop panel made in Germany Scott: more durable, high-temperature resistance and never fading.

Model	TS-800-1
Adjustable power	320W - 3400W (Left:1200W, Right: 2200W)
Voltage	220 V - 50 Hz
Dimensions (mm)	734 x 435 x 90
Net Weight	11.1 kgs
Placket size (mm)	666 x 402

Model	SW-350 TT
Power	3500 kw
Mode	Press Stand
Control	Tunning Knob 9 Adustment
Ceran Glass	288x288
Unit	350x415x120 mm
Net W	6.5 kg



Model	SW-350 BI
Power	3500 kw
Mode	Built-In
Control	Tunning Knob 9 Adustment
Ceran Glass	350x350
Unit	350x350x100 mm
Net W	4.8 kg



Model	SW-350 WTT
Power	3500 kw
Mode	Free Stand
Control	Tunning Knob 9 Adustment
Ceran Glass	C311
Unit	404x350x168 mm
Net W	7.9 kg



Model	SW-350 WBI
Power	3500 kw
Mode	Built-In
Control	Tunning Knob 9 Adustment
Ceran Glass	C311
Unit	365x365x190 mm
Net W	8.2 kg



Model	TSI-888
Adjustable power	5600 W
Voltage	220V ~ 50 Hz
Dimensions (mm)	580x510x85
Net Weight	14 Kgs
Placket size (mm)	558x488



STW-500 FBI / STW-800 FBI

- 5KW/8KW Flat Top Module
- German Scott Ceran / Logic Control System
- Touch Sensor Control, LCD Display w / 12 Adjust Level
- Anti Over Heat, Voltage and Steam Protection
- 60Sec Auto Shut off System / 380V 3 Phase Power
- Cut Out 310x310mm / Net W 18 Kg
- Ceran Glass 500 x 500 mm



STW-500 WBI / STW-800 WBI

- 5KW/8KW Wok Module, German Scott Ceran
- Logic Control System, Ceran Wok 311 mm
- LCD Display w / 12 Adjustable Level
- Anti Over Heat, Voltage and Steam Protection
- 60 Sec Auto Shut off System / 380V 3 Phase Power, International Safety Approval
- Cut Out 310x310mm / Net W 18 Kg



MITTAL INTERNATIONAL

7, Netaji Subhash Marg, Darya Ganj, New Delhi-110002 Ph. : 23271810, 23279639, 23278741, 23242500-1-2-3, 9312210731
Fax: 011-23271218 E-mail : mitalin@del2.vsnl.net.in Website : www.mitalin.com

MUMBAI OFFICE :

171, Udyog Bhawan, Sonawala Road, Goregaon (E), Mumbai-400063. Phone: 26863195, 26861938, 9322233218 Fax : 26867171